



Features and benefits:

- Keyboardcontroller for up to 128 keys
- Version -W with connection for secondary keyboard
- Outputs for Num-, Caps-, Scroll-Lock Full-N-Key rollover and integrated beeper Customizing on request

Specification

Max. Key-Nr.:	128
Inputs:	key matrix (max:) additional keyboard (only -W-version)
Interfaces:	AT; PS/2
Dimensions:	98 x 58 x 12 mm; 3.85" x 2.28" x 0.47"
Weight:	40 g
Operating Temp:	-40°C to +90°C; -40 °F to +194 °F

Cat.-No.	Product Name	
Hardware		
KC05000	TKC-5000-PS2/AT	Keyboard controller
KC05100	TKC-5000-AT-W	with electr. wedge
Software in processor EPROM (AT89C51):		
KP05000	PROG-5000	Keyboard code program (105 keys)
Accessories:		
KK04020	TKK-4020-KABEL-TASTATURMATRIX	Input cable for matrix 8x16
KK05400	TKK-5400-PS/2	PS/2-cable
KW05002	TKC-5000-MANUAL-US	Technical manual, US
KW05001	TKC-5000-MANUAL-GER	Technical manual, German
Programming of your matrix code table by Indukey (Setup Costs)		
RK00001	RKC-GRUNDPREIS	Special programming basis charge
RK00002	RKC-EINTRAGSPREIS	Special programming per entry

