



Features and benefits:

- Gold-on-gold domes
- Extreme temperature range of -40°C to +90°C
- Positive tactile feedback
- Integrated mouse button
- PS/2 and USB compatible
- 19 inch 1U drawer compatible units
- Rugged construction for reliable functionality
- Special Dura-coating for excellent mechanical and chemical resistance
- Ergonomic design
- IP68 sealing, can be submerged in liquid
- 2 million operations per key

Specification Keyboard

Number of Keys:	86
Keyswitch Technology:	gold-on-gold domes
Activation Force/ -Travel:	3,0 N / 0,35 mm
Keyswitch Lifetime:	2 mil. Operations
Protection Level:	IP68, NEMA 6P
Mounting Type:	desktop
Dimensions:	320 x 147 x 20 mm 12,6" x 5,79" x 0,79"
Weight:	950 g
Operating Temperature:	-40 °C to 90 °C; -40 °F to +194 °F

Specification Mousebutton

Number of keys:	2
Motion detection method:	hall sensor
Resolution:	800 dpi
Protection Level:	IP68, NEMA 6P
Enclosure Colour:	similar RAL9002

Cat.-No.	Product Name
KG13001	TKG-086-MB-IP68-GREY-PS/2-US grey; PS/2; US-Layout
KG13003	TKG-086-MB-IP68-GREY-USB-US grey; USB; US-Layout
Other language versions/interfaces/configuration available on request	