



Features and benefits:

- Ex-approval keyboard II 2 G EEx ia IIC T4 / II 2D T79°C IP68
- Barrier always necessary to fulfil the EX-approvals
- Short travel keys
- Extreme temperature range of -40°C to +90°C
- Separate optical mouse available
- 19 inch drawer compatible units
- Special Dura-coating for excellent mechanical and chemical resistance
- Ergonomic design
- IP68 sealing, can be submerged in liquid
- Semi or full customisation available
- Rugged construction for reliable functionality

Specification Keyboard

Number of keys:	105
Keyswitch Technology:	short travel keys
Actuation Force/ -Travel:	3.0 N / 0.3 mm
Keyswitch Lifetime:	3 mil operations
Protection Level:	IP69k, NEMA 6 + 6P
Mounting Type:	desktop
Electronic Interface:	PS/2
Dimensions:	387 x 150 x 20 mm; 15.24" x 5.90" x 0.79"
Weight:	1400g
Operation Temperature:	-20 °C to +50 °C; -4 °F to +122 °F
Enclosure Material:	silicone, aluminium (rearside)

Cat.-No.	Product Name	
KG14046	TKG-105-EX-IP68-GREY-PS/2-US	GREY; PS/2; US-Layout
KA08201	TKA-INTERFACE-EX	Barrier (Current Limiting Unit)
Other language versions/interfaces/configuration available on request		