



Features and benefits:

- Robust and durable
- Silicone switching elements
- PS/2 and USB compatible
- Panel-mount version with mounting studs on rear-side
- Laser engraved key legends for excellent durability
- Non removable keycaps
- High operating comfort and good tactile feedback
- IP65 (NEMA 4x) sealing, water and dust proof
- >10 million operations per key
- Activation force 1 N / key travel 1.5 mm
- Semi or full customisation available
- Kiosk designed web- and e-mail-hot keys

Specification

Number of Keys:	68
Keyswitch Technology:	silicone switching element
Actuation Force/-Travel:	1 N / 1,5 mm
Keyswitch Lifetime:	10 mil. Operations
Protection Level:	IP65; NEMA 4x
Mounting Type:	panel mount
Dimensions:	300 x 125 x 26 mm; 11.81 x 4.92 x 1.02"
Weight:	1600 g
Operating Temperature:	-40 °C to 90 °C; -40 °F to +194 °F
Frontplate Material:	stainless steel

Cat.-No.	Product Name
KV03005	TKV-068-MODUL-PS/2-US PS/2; US-Layout
KV03007	TKV-068-MODUL-USB-US USB; US-Layout
KY13002	TKY-068-MODUL-GASKET Gasket
Other language versions/interfaces/configuration available on request	

