



Features and benefits:

- Robust and durable
- Silicone switching elements
- PS/2 and USB compatible
- Panel-mount version with mounting studs on rear-side
- Laser engraved key legends for excellent durability
- Non removable keycaps
- High operating comfort and good tactile feedback
- IP65 (NEMA 4x) sealing, water and dust proof
- >10 million operations per key
- Actuation force 1 N / key travel 1.5 mm
- Semi or full customisation available

Specification

Number of Keys:	84
Keyswitch Technology:	silicone switching element
Actuation Force/-Travel:	1 N / 1,5 mm
Keyswitch Lifetime:	10 mil. operations
Protection Level:	IP65; NEMA 4x
Mounting Type:	panel mount
Dimensions:	295 x 145 x 30 mm; 11.614" x 5.708" x 1.181"
Weight:	1700 g
Operating Temperature:	-40 °C to 90 °C; -40 °F to +194 °F
Frontplate Material:	stainless steel

Cat.-No.	Product Name	
KV01209	TKV-084-MODUL-PS/2-US	PS/2; US-Layout; compact version
KV01215	TKV-084-MODUL-USB-US	USB; US-Layout; compact version
KY13000	TKY-084-MODUL-GASKET	Gasket
Other language versions/interfaces/configuration available on request		

